

Panic Exit Devices

Strength & Durability | Simplicity | Innovation | Aesthetics

80 Series Features:

- Maintenance-free Design.
- Easy installation, quick retrofit.
- Made of the finest component materials.
- Non-handed available.
- Multiple through-bolt options.
- Keying accomplished without removing device from door.

3828 Series Surface Vertical Rod Exit Device



Rugged exit device in surface vertical rod design.

Specifications:

- For Doors: 1-3/4" (44.5mm) thick standard. 4-1/2" (114mm) minimum stile width required for single or double door applications using standard 641 strike.
- Outside Trim: GTB, HTB, OB, LB, LL, LP or TP trim available.
- Mounting: Furnished standard with wood and machine screws; Available with through bolts and mortise nuts.
- Cover: Nonferrous alloy.
- Chassis: Nonferrous alloy.
- Rail Assembly: Roll formed steel.
- Hand: Non-handed.
- Latchbolt: Stainless steel 3/4" (19mm) throw.
- Strike: 641 packed standard.
- Dogging Feature: Allen-type key furnished standard.
- Finish: PEB, PED, PEN, PEAB.

Ideally suited for:

- Warehouses.
- Fire exits from stairwells in office buildings.

30 Series Features:

- Rugged exit device.
- Easy installation and maintenance.
- Tapered push rail and angled covers.
- Available in four different function with various trim selections.

8800 Rim Exit Device



Reversible rim exit device that sets the industry standard for durability and reliability.

Features:

- Designed for standard width stile applications on wood and metal doors.
- Most functions are non-handed.
- Single point rim latching device.
- Single door & double door applications with mullions.
- Quiet operation and solid security.
- Devices are ANSI A156.3 - 2001 Grade 1.
- UL Fire and Panic listed.

Specifications:

- Door Types: Wood or metal 1-3/4" (44mm) Thick Door; Over 1-3/4" specify thickness and order as a 31- Prefix 4-1/2" (114mm) minimum stile.
- Door Widths:
 - E Rail - 24" to 32" (61cm to 81cm) No cutting required for 32" door;
 - F Rail - 33" to 36" (84cm to 91cm) No cutting required for 36" door
 - J Rail - 37" to 42" (94cm to 107cm) No cutting required for 42" door;
 - G Rail - 43" to 48" (110cm to 122cm) No cutting required for 48" door

- Strike: 649 Standard Black Nylon Coated
 - Optional Strikes: 642, 644 and 613
- Dogging Feature: Hex key dogging standard; Cylinder dogging available (16-).
- Electric Options: AL-, PL-, TL-, 53-, 54-, 55-, 56-, 57-, 58-, 59-.
- Mounting Fasteners: Supplied standard with wood and machine screws; Available with through-bolts and mortise (sex) nuts.
- Latch Bolt: Stainless steel, 3/4" (19mm) throw.
- Device Centerline from Finished Floor: 41" (1041 mm).
- Center Case Dimensions: 8-3/8" (213mm) x 2-5/8" (67mm).
- Projection: Pushbar Neutral - 3" (76 mm); Pushbar Depressed - 2-1/8" (54 mm).

Ideally suited for:

- Single exterior doors.
- Pairs of doors with removable mullion.
- Schools.
- Hospitals.
- Offices.