



6500 Line

The SARGENT 6500 Line is a standard duty key-in-lever lockset designed to exceed the requirements of ANSI A156.2 Series 4000 and Grade 2.

6500 Line

Specifications

- For Doors: 1-3/8" (35mm) to 1-3/4" (44mm) only
- Backset: 2-3/4" (70mm) standard;
2-3/8" (60mm) optional (20- Prefix)
- Cylindrical Housing: Steel zinc dichromate finish
- Front: Wrought brass and stainless steel;
2-1/4" (57mm) x 1-1/8" (29mm)
- Strike:
600 Curved Lip, Brass or Stainless Steel Standard
808 ANSI Curved Lip available (28- prefix)
505 Full Lip strike available (14- prefix)
- Hand: Universal, not handed
- Latch: Brass 1/2" (13mm) throw
- Keys: Two, nickel silver
- Cylinder: Brass, 6 pin, LA keyway standard
- Finishes : 3, 4, 10, 10B, 26, 26D
(No Split Finish)
- Door Prep: ANSI A115.2 (161) Modified
- Minimum Stile: 4-1/2" (114mm)

Certification Compliance

- Meets ANSI A156.2 Series 4000 – Grade 2
- UL listed to U.S.A. and Canadian safety standards. Listed for 3 Hour Doors
- Meets UL 10C and UBC 7-2 (1997)
- All levers conform to ADA requirement for barrier-free accessibility
- Levers conform to California Administrative Code Title 19 and 24
- All individual components of a total door opening are required to comply with each code